



Features

- Onboard Intel® Atom SoC E3845 1.91 GHz
- Full Flat Front Panel with Projected Capacitive Touch Supports Multi Touch
- Intel® 1211AT Gigabit Ethernet, 5.1-CH Audio
- 1 x VGA, 1 x HDMI, 2 x LAN, 1 x CF Slot, 2 x COM, 1 x USB 3.0, 3 x USB 2.0
- Fanless System & VESA Compliance
- Wide Voltage +12V ~ +26V Input, ErP Power
- Timer-Power-On
- Front Side IP65 Dust and Water Proof
- Optional WiFi Module



Specifications

Panel

LCD Size	10.1"
Resolution	1024 x 600
Pixel pitch	0.2175 (H) x 0.2088 (V)
Luminance	200cd/m ²
Contrast ratio	500
Viewing angle	20 (U), 45 (D), 45 (L), 45 (R)
Response time	7ms
Backlight	LED
Touch Type	Projective Capacitive
Touch Light Transmission	86%
Touch Controller	USB touch (EETI)

System

SBC	ECM-BYT
Processor	Intel® Atom™ SoC E3845 4-Core 1.91 GHz processor
System Chipset	Intel® Valleyview SoC
I/O Chipset	EC ITE IT8528E
System Memory	1 x 204-Pin DDR3L 1066MHz SO-DIMM up to 8 GB or 204-Pin DDR3L 1333MHz SO-DIMM up to 8 GB Processor E3845 only support 1333MHz
Watchdog Timer	H/W Reset: 1sec.~255min. and 1sec. or 1min./step

Expansion & Storage

Expansion	1 x Mini PCIe Supports mSATA
Storage	1 x CompactFlash Type I/II Socket 1 x 2.5" Drive Bay

I/O

USB	3 x USB 2.0 1 x USB 3.0
COM Port	1 x RS-232 1 x RS-232/422/485

Audio

Chipset	Realtek ALC892, Support 5.1-CH
Audio Interface	Line-Out

Ethernet

Chipset	2 x Intel® I211AT
Ethernet Interface	10/100/1000 Base-Tx GbE compatible
LAN Port	2 x RJ-45

Power Requirement

Power Requirement	+12V ~ +26V
Power Type	AT/ATX
Adapter	Input: 100 ~ 240Vac/ 50 ~ 60Hz Output: 60W Adapter (12V @ 5A Adapter) AC-DC Adapter

Mechanical & Environmental

System Fan	Fanless
Construction - Front	Silver Aluminum
Construction - Rear	Black
Dimension	251.94 x 154.5 x 45.25 mm
Weight	1.2 Kgs
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Storage Temperature	-10°C ~ 50°C (14°F ~ 122°F)
Operating Humidity	0% ~ 90% Relative Humidity, Non-condensing
Vibration Test	With SSD/mSATA : 1.5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 30min/axis
Shock Test	With CF/SSD : 10Grms, IEC 60068-2-27, Half Sine, 11ms

Certifications & Software Support

Certification	CE
Information	FCC Class B
OS Information	Win 7, Win 8, Linux

Ordering Information

BFC-10W9-384-A1R

Intel® Atom™ SoC E3845 1.91GHz / 1G DDR3L / 2LAN / 2COM / 4USB / 12~26V Input / 12V Adaptor