


## FAQ / Application Note

Subject: How to connect AUX-001 daughter board with EPI-QM57				
FAQ Document No: H13012	Date: 2013/04/22			
Model Name. EPI-QM57	Rev. A1			
Category: ☐General ☐H/W ☐S/W ☐Others, ☐ I/O Interface				
Purpose:  To expand USB port by use AUX-001 daughter board with EPI-QM57.				

Below is the layout and pin defining schematic diagram for 3 USB port socket on ECM-CDV (Hardware Version A).

## 2.4.22 USB connector 4&5/ 6&7 (JUSB1/ JUSB2)



		1
_		
		0

Signal	PIN	PIN	Signal	
+5V	1	2	GND	
USB_DN4/6	3	4	GND	
USB_DP4/6	5	6	USB_DP5/7	
GND	7	8	USB_DN5/7	
GND	9	10	+5V	


Note: Wrong USB cable configuration with your USB devices might cause your USB devices damaged.


**Avalue Technology Inc.** 

7F, 228, Lian-Cheng Road, Chung Ho City, Taipei, Taiwan R.O.C.



Step 1: The red word 1 is pin 1 of USB port socket. To connect cable on board and the red line is connect to pin 1. The other end of cable to connect to USB port socket of daughter board, and the red circle is power Vcc, please connect red line of cable to this pin.





**Avalue Technology Inc.** 

7F, 228, Lian-Cheng Road, Chung Ho City, Taipei, Taiwan R.O.C.



Step 2: The complete picture.

